

冷間圧延ステンレス鋼板

SUS304/SUS304L/SUS316/SUS316L

単位:mm

厚さ	幅1,000	幅1,219	幅1,524
0.3	●		
0.4	●		
0.5	●	●	
0.6	●	●	
0.8	●	●	
1	●	●	●
1.2	●	●	●
1.5	●	●	●
2	●	●	●
2.5	●	●	●
3	●	●	●
4	●	●	●
5	●	●	●
6	●	●	●

長さ(mm) : 2,000 / 2,438 / 3,048 / 4,000 / 6,100

表面: 2B / HL / #400

※上記寸法以外へのスケッチサイズ対応可能

熱間圧延ステンレス鋼板

SUS304/SUS304L/SUS316/SUS316L

単位:mm

厚さ/寸法	1,000×2,000	1,219×2,438	1,524×3,048	1,524×4,000	1,524×6,100	2,000×6,100	2,438×6,100
3	● ※	● ※	● ※	● ※	● ※		
4	● ※	● ※	● ※	● ※	● ※	●	●
5	● ※	● ※	● ※	● ※	● ※	●	●
6	● ※	● ※	● ※	● ※	● ※	●	●
8	● ※	● ※	● ※	● ※	● ※	●	●
9	● ※	● ※	● ※	● ※	● ※	●	●
10	●	●	●	●	●	●	●
12	●	●	●	●	●	●	●
14			●	●	●	●	●
15			●	●	●	●	●
16			●	●	●	●	●
18						●	●
19						●	●
20						●	●
22						●	●
25						●	●
28						●	●
30						●	●
32						●	●
35						●	●
38						●	●
40						●	●
45						●	●
50						●	●
55							●
60							●
65							●
70						●	

長さ(mm): 2,000 / 2,438 / 3,048 / 4,000 / 6,100

※上記寸法以外へのスケッチサイズ対応可能