

# SUS304L TPA

単位:mm

サイズ 外径×厚さ	長さ	単重 (Kg/m)
13.8× 2.0	4,000	0.588
17.3× 2.0	4,000	0.762
17.3× 3.0	4,000	1.07
21.7× 2.0	4,000	0.981
21.7× 2.5	4,000	1.20
21.7× 3.0	4,000	1.40
27.2× 2.0	4,000	1.26
27.2× 2.5	4,000	1.54
27.2× 3.0	4,000	1.81
34.0× 2.0	4,000	1.59
34.0× 3.0	4,000	2.32
34.0× 3.5	4,000	2.66
34.0× 4.0	4,000	2.99
42.7× 2.0	4,000	2.03
42.7× 3.0	4,000	2.97
42.7× 3.5	4,000	3.42
42.7× 4.0	4,000	3.86
48.6× 2.0	4,000	2.32
48.6× 3.0	4,000	3.41
48.6× 3.5	4,000	3.93
48.6× 4.0	4,000	4.44
60.5× 2.0	4,000	2.91
60.5× 3.0	4,000	4.30
60.5× 3.5	4,000	4.97
60.5× 4.0	4,000	5.63
76.3× 3.0	4,000	5.48
76.3× 3.5	4,000	6.35
76.3× 4.0	4,000	7.20
76.3× 5.2	4,000	9.21
89.1× 2.0	4,000	4.34
89.1× 3.0	4,000	6.43
89.1× 4.0	4,000	8.48
89.1× 5.5	4,000	11.5
101.6× 2.0	4,000	4.96
101.6× 3.0	4,000	7.37
114.3× 3.0	4,000	8.32
114.3× 4.0	4,000	11.0
114.3× 6.0	4,000	16.2
139.8× 3.0	4,000	10.2
139.8× 3.5	4,000	11.9
139.8× 4.0	4,000	13.5
139.8× 5.0	4,000	16.8
139.8× 6.6	4,000	21.9
165.2× 3.0	4,000	12.1
165.2× 3.5	4,000	14.1
165.2× 4.0	4,000	16.1
165.2× 5.0	4,000	20.0
165.2× 7.1	4,000	28.0
216.3× 3.0	4,000	15.9
216.3× 4.0	4,000	21.2
216.3× 6.5	4,000	34.0
216.3× 8.2	4,000	42.5
267.4× 4.0	4,000	26.2

単位:mm

サイズ 外径×厚さ	長さ	単重 (Kg/m)
267.4× 6.5	4,000	42.2
267.4× 9.3	4,000	59.8
318.5× 4.0	4,000	31.3
318.5× 4.5	4,000	35.2
318.5× 6.5	4,000	50.5
318.5×10.3	4,000	79.1